

Supplier Part Number	SXT632 Series						
Product Description	6.0mm X 3.5mm SMD Crystal						
Product Revision							
Product Total Weight	0.104g/pcs						
Contact Information	Company	Suntsu Frequency Control, Inc.					
	Contact Name	KH Mun					
	Address	142 Technology Dr., Suite 150 Irvine, CA 92618					
	Phone Number	949-305-0220					
Homogenous Component/ Subcomponent	Homogenous Component/ Subcomponent Weight (g)	Substance		Substance Weight (g)	PPM Level (If Available) (Substance Weight/Total Homogenous Component or Subcomponent Weight*1000000)	PPM Level Availability Date (If Not Available)	Purpose/Location
6035 PKG	0.0530	Alumina-Al ₂ O ₃	1344-28-1	0.0364640000	350615.385		Ceramic
		Silica SiO ₂	14808-60-7	0.0021200000	20384.615		Ceramic
		Molybdenum-Mo	7439-98-7	0.0003180000	3057.692		Ceramic
		Titanium oxide-TiO	7440-32-6	0.0000530000	509.615		Ceramic
		Magnesia-MgO	1309-48-4	0.0004240000	4076.923		Ceramic
		Calcia-CaO	1305-78-8	0.0003710000	3567.308		Ceramic
		Tungsten-W	7440-33-7	0.0028620000	27519.231		Electric conductor
		Molybdenum-Mo	7439-98-7	0.0001060000	1019.231		Electric conductor
		Silver-Ag	7440-22-4	0.0010600000	10192.308		Brazing material
		Copper-Cu	7440-50-8	0.0004240000	4076.923		Brazing material
		Iron-Fe	7439-89-6	0.0041340000	39750.000		Kovar ring
		Nickel-Ni	7440-02-0	0.0022260000	21403.846		Kovar ring
		Cobalt-Co	7440-48-4	0.0013250000	12740.385		Kovar ring
		Nickel-Ni	7440-02-0	0.0006890000	6625.000		Ni plating
Cobalt-Co	7440-48-4	0.0002650000	2548.077		Ni plating		
Gold-Au	7440-57-5	0.0001590000	1528.846		Au plating		
LID	0.03	Iron-Fe	7439-89-6	0.0159690000	153548.077		Alloy
		Nickel-Ni	7440-02-0	0.0088470000	85067.308		Alloy
		Cobalt-Co	7440-48-4	0.0050280000	48346.154		Alloy
		Manganese-Mn	7439-96-5	0.0001170000	1125.000		Alloy
		Silicon-Si	7440-21-3	0.0000240000	230.769		Alloy
		Copper-Cu	7440-50-8	0.0000150000	144.231		Alloy
Blank	0.003	Silica SiO ₂	14808-60-7	0.0030000000	28846.154		Quartz crystal
Silver	0.013	Silver-Ag	7440-22-4	0.0129991160	124991.500		Electrode
		Copper-Cu	7440-50-8	0.0000003900	3.750		Electrode
		Bismuth-Bi	7440-69-9	0.0000001040	1.000		Electrode
		Iron-Fe	7439-89-6	0.0000001300	1.250		Electrode
		Antimony-Sb	7440-36-0	0.0000001300	1.250		Electrode
		Selenium-Se	7782-49-2	0.0000000650	0.625		Electrode
		Tellurium-Te	13494-80-9	0.0000000650	0.625		Electrode
Epoxy	0.005	Silver-Ag	7440-22-4	0.0042500000	40865.385		Connect
		Silicone Resin		0.0007500000	7211.538		Support
				0.10400	1000000.000		